AMENDMENTS TO THE CLAIMS

This listing of claims will replace all prior versions and listings of claims in the

application:

LISTING OF CLAIMS:

1.   (currently amended): A communication terminal device comprising:

display means for displaying information such as characters;

input means for receiving input of operation information;

processing means for generating said information based on operation information

of the input means; and

light-emitting means for lighting at least either said display means or said input

means;

reception means for receiving ~~contents~~ data described in a predetermined

information description language based on said operation information;

code detection means for detecting a predetermined code indicative of the end of

~~contents~~ data received by the reception means; and

light-emission control means for stopping light-emission by said light-emitting

means upon start of the reception of said ~~contents~~ data by said reception means and starting light-

emission by said light-emitting means upon detection of said predetermined code by said code

detection means.

2

2.   (currently amended): The communication terminal device as set forth in claim 1,

comprising:

communication type determination means for determining whether call is to be

made by voice information or said ~~contents~~ data is to be received, and

light-emission control means for, when the determination is made by said

communication type determination means that said call is to be made, stopping light-emission by

said light-emitting means upon start of said call and starting light-emission by said light-emitting

means upon end of said call and when the determination is made by said communication type

determination means that said ~~contents~~ data is to be received, stopping light-emission by said

light-emitting means upon start of the reception of said ~~contents~~ data by said reception means

and starting light-emission by said light-emitting means upon detection of said predetermined

code by said code detection means.

3.   (original): The communication terminal device as set forth in claim 1, comprising:

time counting means for starting counting time from when said operation

information is input by said input means, and

light-emission stop means for stopping light-emission by said light-emitting

means when time counted by the time counting means overs a lighting time set in advance.

4.   (currently amended): The communication terminal device as set forth in claim 1,

comprising:

communication type determination means for determining whether call is to be

made by voice information or said ~~contents~~ data is to be received,

light-emission control means for, when the determination is made by said

communication type determination means that said call is to be made, stopping light-emission by

said light-emitting means upon start of said call and starting light-emission by said light-emitting

means upon end of said call and when the determination is made by said communication type

determination means that said ~~contents~~ data is to be received, stopping light-emission by said

light-emitting means upon start of the reception of said ~~contents~~ data by said reception means

and starting light-emission by said light-emitting means upon detection of said predetermined

code by said code detection means,

time counting means for starting counting time from when said operation

information is input by said input means, and

light-emission stop means for stopping light-emission by said light-emitting

means when time counted by the time counting means overs a lighting time set in advance.

5.   (currently amended): The communication terminal device as set forth in claim 1,

wherein

said reception means

4

receives ~~contents~~ data described in an information description language such as a

hypertext markup language or a wireless markup language, and said code detection means

detects a predetermined end tag indicative of the end of ~~contents~~ data received by said reception

means.

6.   (currently amended): The communication terminal device as set forth in claim 1,

wherein

said reception means receives ~~contents~~ data described in an information

description language such as a hypertext markup language or a wireless markup language, and

said code detection means detects a predetermined end tag indicative of the end of ~~contents~~ data

received by said reception means, and which further comprises:

time counting means for starting counting time from when said operation

information is input by said input means, and

light-emission stop means for stopping light-emission by said light-emitting

means when time counted by the time counting means overs a lighting time set in advance.

7.   (currently amended): The communication terminal device as set forth in claim 1,

comprising:

communication type determination means for determining whether call is to be

made by voice information or said ~~contents~~ data is to be received, and

5

light-emission control means for, when the determination is made by said

communication type determination means that said call is to be made, stopping light-emission by

said light-emitting means upon start of said call and starting light-emission by said light-emitting

means upon end of said call and when the determination is made by said communication type

determination means that said ~~contents~~ data is to be received, stopping light-emission by said

light-emitting means upon start of the reception of said ~~contents~~ data by said reception means

and starting light-emission by said light-emitting means upon detection of said predetermined

code by said code detection means, wherein

said reception means

receives ~~contents~~ data described in an information description language such as a

hypertext markup language or a wireless markup language, and said code detection means

detects a predetermined end tag indicative of the end of ~~contents~~ data received by said reception

means.

8.   (currently amended): The communication terminal device as set forth in claim 1,

comprising:

communication type determination means for determining whether call is to be

made by voice information or said ~~contents~~ data is to be received,

light-emission control means for, when the determination is made by said

communication type determination means that said call is to be made, stopping light-emission by

said light-emitting means upon start of said call and starting light-emission by said light-emitting

means upon end of said call and when the determination is made by said communication type

determination means that said ~~contents~~ data is to be received, stopping light-emission by said

light-emitting means upon start of the reception of said ~~contents~~ data by said reception means

and starting light-emission by said light-emitting means upon detection of said predetermined

code by said code detection means,

time counting means for starting counting time from when said operation

information is input by said input means, and

light-emission stop means for stopping light-emission by said light-emitting

means when time counted by the time counting means overs a lighting time set in advance,

wherein

said reception means

receives ~~contents~~ data described in an information description language such as a

hypertext markup language or a wireless markup language, and said code detection means

detects a predetermined end tag indicative of the end of ~~contents~~ data received by said reception

means.

9.   (original): The communication terminal device as set forth in claim 1, wherein

said light-emission control means, at the time of stopping light-emission by said

light-emitting means, stops light-emission after a lapse of a predetermined wait time.

10.   (currently amended): A communication terminal device comprising:

display means for displaying information such as characters;

input means for receiving input of operation information;

processing means for generating said information based on operation information

of the input means; and

light-emitting means for lighting at least either said display means or said input

means;

reception means for receiving ~~contents~~ data described in a predetermined

information description language expressing one ~~contents~~ data by a plurality of cards based on

said operation information;

code detection means for detecting a card end tag indicative of the end of each

said card of the ~~contents~~ data received by the reception means; and

light-emission control means for stopping light-emission by said light-emitting

means upon start of the reception of said ~~contents~~ data by said reception means and starting light-

emission by said light-emitting means upon detection of said card end tag by said code detection

means.

11.   (currently amended): The communication terminal device as set forth in claim 10,

wherein

said reception means receives ~~contents~~ data described in a wireless markup language.

12.   (currently amended): The communication terminal device as set forth in claim 10,

further comprising

detection tag setting means for in advance setting either an end tag indicative of

the end of said ~~contents~~ data or a card end tag indicative of the end of each said card to be

detected, wherein

said code detection means detects a tag set by said detection tag setting means

from the ~~contents~~ data received by said reception means, and

said light-emission control means stops light-emission by said light-emitting

means upon start of the reception of said ~~contents~~ data by said reception means and starts light-

emission by said light-emitting means upon detection of a tag set by said detection tag setting

means by means of said code detection means.

13.   (currently amended): The communication terminal device as set forth in claim 10,

wherein

said reception means receives ~~contents~~ data described in a wireless markup

language, and which further comprises

detection tag setting means for in advance setting either an end tag indicative of

the end of said ~~contents~~ data or a card end tag indicative of the end of each said card to be

detected, and wherein

said code detection means detects a tag set by said detection tag setting means

from the ~~contents~~ data received by said reception means, and

said light-emission control means stops light-emission by said light-emitting

means upon start of the reception of said ~~contents~~ data by said reception means and starts light-

emission by said light-emitting means upon detection of a tag set by said detection tag setting

means by means of said code detection means.

14.   (original): The communication terminal device as set forth in claim 10,

comprising:

time counting means for starting counting time from when said operation

information is input by said input means, and

light-emission stop means for stopping light-emission by said light-emitting

means when time counted by the time counting means overs a lighting time set in advance.

15.   (currently amended): The communication terminal device as set forth in claim 10,

comprising:

time counting means for starting counting time from when said operation

information is input by said input means, and

light-emission stop means for stopping light-emission by said light-emitting

means when time counted by the time counting means overs a lighting time set in advance,

wherein

said reception means receives ~~contents~~ data described in a wireless markup

language.

16.   (currently amended): The communication terminal device as set forth in claim 10,

comprising:

time counting means for starting counting time from when said operation

information is input by said input means,

light-emission stop means for stopping light-emission by said light-emitting

means when time counted by the time counting means overs a lighting time set in advance, and

detection tag setting means for in advance setting either an end tag indicative of

the end of said ~~contents~~ data or a card end tag indicative of the end of each said card to be

detected, wherein

said code detection means detects a tag set by said detection tag setting means

from the ~~contents~~ data received by said reception means, and

11

said light-emission control means stops light-emission by said light-emitting

means upon start of the reception of said ~~contents~~ data by said reception means and starts light-

emission by said light-emitting means upon detection of a tag set by said detection tag setting

means by means of said code detection means.

17.   (original): The communication terminal device as set forth in claim 10, wherein

said light-emission control means, at the time of stopping light-emission by said

light-emitting means, stops light-emission after a lapse of a predetermined wait time.

18.   (currently amended): A display control method in a communication terminal

device having display means for displaying information such as characters, input means for

receiving input of operation information, processing means for generating said information based

on operation information of the input means, and light-emitting means for lighting at least either

said display means or said input means, comprising the steps of:

receiving ~~contents~~ data described in a predetermined information description

language based on said operation information;

detecting a predetermined code indicative of the end of received ~~contents~~ data;

and

stopping light-emission by said light-emitting means upon start of the reception of

said ~~contents~~ data and starting light-emission by said light-emitting means upon detection of said

predetermined code.

19.   (currently amended): The display control method in a communication terminal

device as set forth in claim 18, comprising the steps of:

determining whether call is to be made by voice information or said ~~contents~~ data

is to be received, and

when the determination is made that said call is to be made, stopping light-

emission by said light-emitting means upon start of said call and starting light-emission by said

light-emitting means upon end of said call and when the determination is made that said ~~contents~~

data is to be received, stopping light-emission by said light-emitting means upon start of the

reception of said ~~contents~~ data and starting light-emission by said light-emitting means upon

detection of said predetermined code.

20.   (original): The display control method in a communication terminal device as set

forth in claim 18, comprising the steps of:

counting the time from when said operation information is input by said input

means, and

13

stopping light-emission by said light-emitting means when counted time overs a

lighting time set in advance.

21.   (currently amended): A display control method in a communication terminal

device having display means for displaying information such as characters, input means for

receiving input of operation information, processing means for generating said information based

on operation information of the input means, and light-emitting means for lighting at least either

said display means or said input means, comprising the steps of:

receiving ~~contents~~ data described in a predetermined information description

language expressing one ~~contents~~ data by a plurality of cards based on said operation

information;

detecting a card end tag indicative of the end of each said card of received

~~contents~~ data; and

stopping light-emission by said light-emitting means upon start of the reception of

said ~~contents~~ data and starting light-emission by said light-emitting means upon detection of said

card end tag.

22.   (currently amended): The display control method in a communication terminal

device as set forth in claim 21, wherein

~~contents~~ data described in a wireless markup language is received.

14

23.   (currently amended): The display control method in a communication terminal

device as set forth in claim 21, further comprising the steps of:

in advance setting either an end tag indicative of the end of said ~~contents~~data or a

card end tag indicative of the end of each said card to be detected,

detecting a set tag from received ~~contents~~ data, and

stopping light-emission by said light-emitting means upon start of the reception of

said ~~contents~~ data and starting light-emission by said light-emitting means upon detection of a set

tag.

24.   (original): The display control method in a communication terminal device as set

forth in claim 21, further comprising the steps of:

counting time from when said operation information is input by said input means,

and

stopping light-emission by said light-emitting means when counted time overs a

lighting time set in advance.

25. (previously presented): A communication terminal device comprising:

a display that displays information;

15

an operator's panel that receives input of operation information;

a processor that generates said information based on said operation information;

a light-emitting circuit that lights said display or said operator's panel;

a receiving circuit that receives data described in a predetermined description language

based on said operation information;

a detecting circuit that detects a predetermined code indicative of the end of data received

by said receiving circuit; and

a controller unit that stops lighting by said light-emitting circuit upon start of the

reception of said data by said receiving circuit and starts lighting by said light-emitting circuit

upon detecting said predetermined code by said detecting circuit.

26.   (new): The communication terminal device as set forth in claim 1, wherein the

interval between said stopping of light-emission by said light-emitting means and said starting of

light-emission by said light-emitting means is configured such that said light-emission does not

appear to be continuous.

27.   (new): The communication terminal device as set forth in claim 10, wherein the

interval between said stopping of light-emission by said light-emitting means and said starting of

light-emission by said light-emitting means is configured such that said light-emission does not

appear to be continuous.

28.   (new): The display control method in a communication terminal device as set

forth in claim 18, wherein the interval between said stopping of light-emission by said light-

emitting means and said starting of light-emission by said light-emitting means is configured

such that said light-emission does not appear to be continuous.

29.   (new): The display control method in a communication terminal device as set

forth in claim 21, wherein the interval between said stopping of light-emission by said light-

emitting means and said starting of light-emission by said light-emitting means is configured

such that said light-emission does not appear to be continuous.

30.   (new): The communication terminal device according to claim 25, wherein the

controller unit is configured so that interval between said stopping lighting by said light-emitting

circuit and said starting lighting by said light-emitting circuit is configured such that said lighting

does not appear to be continuous.